

MARBOS Spezialfuge

SF

Highly flowable fine joint mortar
water impermeable, fast setting, plastic modified



Application areas:



For jointing of paved and slabbed surfaces made of natural stone, concrete blocks, clinker bricks and ceramic coverings that are exposed to light to heavy loads.

Especially for large format coverings.

For the renovation of existing surfaces.

Can also be used in areas exposed to chlorine-treated water (e.g. pool surrounds).

Suitable for use category N1 to N3 according to ZTV Wegebau.

N1: Walkable surface pavements not intended for motor vehicles and comparable uses outside areas of road traffic (e.g. terraces, garden paths, paths in home garden areas, seating areas in parks).

N2: Pavements for vehicles up to 3.5 t permissible total weight outside of road traffic areas (e.g. garage driveways, carports, parking spaces, paths in green areas). Note: not suitable for vehicles with high point loads, e.g. industrial trucks, forklifts, lift trucks, lifting platforms.

N3: Trafficable surface pavements like load category 2, but with occasional traffic of vehicles up to 20 t permissible total weight with wheel loads ≤ 5 t outside of road traffic areas (e.g. care, maintenance and res-cue routes as well as fire department, garage and building access roads).

For joint widths from 1 mm.

Properties:

- For indoors and outdoors
- Water impermeable
- Fast hardening
- Quickly walkable
- Early washable
- High frost/de-icing salt resistance
- Self-compacting
- Highly flowable and slurryable
- Color stable
- Easy cleaning due to Comfort-Clean-System CCS

Material basis:

- SCO-Binder (Special binder)
- Selected fillers and standardized aggregates
- Additives to improve the processing properties

MARBOS Spezialfuge

SF

| | | |
|-----------------|---|---|
| Technical data: | Color | grey, sand, anthracite |
| | Joint width | 1 mm to 8 mm |
| | Joint depth | > 3 cm* For traffic, jointing at full height of the stone. |
| | Processing temperature | > 0°C to + 30 °C |
| | Temperature resistance | - 20 °C to + 80 °C |
| | Water consumption per 20 kg container | ca. 4,7 Liter |
| | Processing time | ca. 30 minutes |
| | Walkability | after ca. 4 hours |
| | Resilient | after ca. 7 days |
| | Adhesive tensile strength | ca. 1,2 N/mm ² |
| | E-module | ca. 16.000 N/mm ² |
| | Frost-de-icing salt resistance according to CDF | < 120 g/m ² Weathering |
| | Compressive strength after 28 days | ≥ 30 N/mm ² |

* In the case of a deformation-resistant mortar bed and a firm bond with the stone or plate as well as foot traffic, the joint depth can also be less, but must not undercut 15 mm.

Substrate preparation:

The substrate must be load-bearing and permanently drainable to withstand the expected traffic loads.
The expected loads must be absorbed. Sagging of the pavement under load will lead to cracking.
To prevent separation layers and to ensure optimum adhesion of the paving joint mortar to the stone flanks, only paving stones that are clean on all sides are to be used.
An inadequately water-permeable superstructure accumulates the water and leads to disturbances in the setting behavior, as well as to damage of the joints when exposed to frost.
Carefully pre-wet the surface to be worked on so that there is no absorbency of the covering material at the time of placing the jointing material.
Standing water must be removed from the joints.
When restoring existing surfaces, make sure that the old joint filling is removed without residue and to the full pavement height. If these existing surfaces are unbound, the bedding material must be chippings. The joint depth must not undercut 2 cm in the case of unbound and exclusively walked-on ceramic surfaces (N 1).
Permanent is the laying in our water-permeable bedding mortar with bonding agent. Increased cracking may occur with unbound bedding.
When used on surfaces subject to traffic, joint filling is required at full joint height. Pre-wet the surface to be jointed thoroughly and, if necessary, several times.
An appropriately dimensioned flex strip must be attached to vertical components to avoid residual stresses. Movement joints from the sub-structure must be transferred to the superstructure.
Depending on the size and geometry of the surface, movement joints must be provided.

MARBOS Spezialfuge

SF

| | |
|------------------------------|---|
| Working: | <p>In a clean mixing vessel, mix thoroughly and lump-free with the specified amount of clean tap water. A stirrer with ca. 600 RPM is recommended.</p> <p>The specified mixing and maturing time must be observed.</p> <p>The paving joint mortar can be processed, after instruction, with the mixing pump Knauf PFT Ritmo L.</p> <p>Spread the compound on the pre-wetted surface and apply to the joints with a rubber wiper or similar without air pockets.</p> <p>For surfaces with steep slopes, staircases, etc., the amount of water added can be reduced slightly to prevent the joints from leaking.</p> <p>While setting, keep the surface damp with spray mist.</p> <p>After the material has set (material in the joint can no longer be pressed in with a finger), the surface is wetted, pre-washed with a hard broom (scrubber) and intensively rewashed. High temperatures reduce the indicated times, low temperatures extend them.</p> |
| Post-treatment: | <p>Appropriate post-treatment of the hardened mortar ensures flawless hardening. For ceramic coverings or e.g. calibrated tiles, roughly prewash the covering after the material has stiffened and then clean with a sponge board. After cleaning, remove any water remaining on the surface to prevent staining from drying cleaning water.</p> |
| Material consumption: | <p>Consumption see table</p> |
| Packaging: | <ul style="list-style-type: none"> • 20 kg bag - 42 pieces/pallet |
| Storage: | <ul style="list-style-type: none"> • Protected from weather, cool and dry on wooden racks. Seal opened containers immediately. • Unopened containers if stored properly 12 months from date of manufacture. • Pallets must not be stacked on top of each other. • Protect containers from direct sunlight. • Low chromate according to directive No. 1907/2006 (REACH) – GHS CODE ZP 1. |
| Waste management: | <p>Hardened product remainders to be wasted as common rubble under code no. 17 09 04.</p> |
| Cleaning: | <p>Depending on the stone condition, a veil may remain after jointing. This can be removed with a suitable cement veil remover (e. g. LITHOFIN MN Zementschleier- und Rostentferner). Please check the compatibility before use, the specifications of the product manufacturer's must be observed.</p> <p>To reduce adhesion on the surface of the covering, we recommend pre-treating the surface to be jointed with an impregnation/grouting aid (e.g. LITHOFIN Basic Protection).</p> <p>The respective technical data sheets must be observed.</p> <p>Immediately clean containers, tools, etc. with water. Cleaning is only possible by mechanical means once the product has hardened.</p> |
| Safety note: | <ul style="list-style-type: none"> • Keep out of the reach of children. • Additional information: see safety data sheet. |
| Note: | <ul style="list-style-type: none"> • The technical data relates to +20 °C and 50 % rel. humidity. Lower temperatures extend the specified values, higher temperatures shorten them. • While the product is setting, protect it against direct sunshine, draughts, frost, driving rain as well as too high (> 30 °C) and too low (< 0 °C) temperatures. • Do not dilute material that is already setting by means of water. |

MARBOS Spezialfuge

SF

Note:

- Differences in color shade may occur, e.g. due to different moisture levels in places from substructures and joint mortar or the environment. We are unable to provide any warranty for such or similar color deviations in the created joint network.
- Paving joint mortars are made from natural raw materials which are subject to natural color variations. Therefore, color differences between different containers do not constitute a reason for objection.
- Only use material from one batch on contiguous surfaces.
- In the case of chamfered paving, the joint may only be filled to the lower edge of the chamfer.
- The instructions of the covering manufacturers must be observed, in particular the installation and maintenance instructions.
- Check compatibility with light-colored stones and with artificial stones (cement- or plastic-bonded) or surface-treated stones!
- For the work to be performed, the relevant recommendations, guidelines, standard and regulations, as well as the generally accepted rules of technology must be observed.
- We recommend in particular to observe the following regulations: **DIN 18318** VOB - Part C: (ATV) - Paved surfaces and plates, edgings, **ZTV-Wegebau** "Additional technical contract conditions for the construction of paths and squares outside road traffic areas"
- In case of doubt, create test surfaces.

Quality control:

Subject to continuous internal and external monitoring.
Production and WPK are certified according to DIN EN ISO 9001.

Consumption overview: ca.- data for a joint depth of 3 cm

| Format [cm] | Joint width [mm] | Consumption [kg/m ²] | Joint width [mm] | Consumption [kg/m ²] |
|-------------|------------------|----------------------------------|------------------|----------------------------------|
| 8 – 9 | 2 | ca. 3,1 | 5 | ca. 7,8 |
| 10 – 11 | 2 | ca. 2,5 | 5 | ca. 6,2 |
| 10 – 20 | 2 | ca. 2,0 | 5 | ca. 4,8 |
| 14 – 17 | 2 | ca. 1,8 | 5 | ca. 4,3 |
| 30 – 30 | 2 | ca. 0,9 | 5 | ca. 2,2 |
| 40 – 40 | 2 | ca. 0,7 | 5 | ca. 1,7 |
| 60 – 60 | 2 | ca. 0,5 | 5 | ca. 1,1 |
| 80 – 40 | 2 | ca. 0,6 | 5 | ca. 1,2 |

The consumption values are approximate values that have been calculated on the basis of our experience. Depending on processing and surface condition, the actual material requirement may deviate.

During execution of work the relevant recommendations and guidelines, rules and standards, relevant technical instruction leaflets as well as the acknowledged rules of architecture and engineering have to be regarded. We do not have any influence on different weather/substrate and object conditions. Our written and spoken application/technological recommendations handed out to customers and craftsmen respectively are without obligation and do not constitute any contractual legal relationship and no lateral duty of a sales contract. All indications and recommendations of technical data sheets refer to standard purpose of use. With the publication of this technical instruction sheet, the previous ones lose their validity. This is a translation. Please refer in any case of misunderstanding the relevant German technical data sheet. Ed 17.02.2023